

SafeNet eToken 5300 Series PKI-based Multi-factor Authenticators



In today's world of on-the-move workforces and mobility, enterprise IT needs to carefully balance security with convenience. Organizations are long-past feeling comfortable with simple user name and passwords being the only protection keeping unwanted intruders from gaining access to networks and identities. That is why more and more businesses depend on Public Key Infrastructure (PKI) to provide the strong security to maintain a safe digital environment.

Ultra-secure MFA—Portable Form Factors

SafeNet eToken 5300 series is an ideal solution for enterprises looking to deploy the military-grade security of PKI, while maintaining a convenient solution for employees. These tokens feature compact, tamper-evident USB with presence detection, which creates a third factor of authentication. Something you have (physical token), something you know (PIN), something you do (touching the token). SafeNet eToken 5300 series provides a state of the art design with durable plastic

SafeNet eToken 5300 is offered in two sizes:

- The Mini form factor features extensive landscape for custom logos or company name.
- The Micro form factor features USB-A connector and is the smallest USB form factor in the industry and is perfect for users who want to leave the token continuously plugged to the port (similar to a USB RF dongle).



SafeNet eToken 5300 holds FIPS 140-2 certification for the full token boundary and Common Criteria EAL 6+ certification at the chip boundary.

SafeNet eToken 5300-C is offered in mini size only:

This new token is based on a new design language which supports USB-C connection and enables landscape for custom logos or company name.



SafeNet eToken 5300 series offers multi-application dynamic smart card functionality. It can be used with any USB connection for Identity and Access Management applications such as network authentication, digital signatures, email encryption and other advanced services based on Public Key Infrastructure (PKI).

Benefits

- Improves productivity by allowing employees and partners to securely access corporate resources
- Adds security capabilities with presence detector sensor
- Enables advanced certificate-based applications, such as digital signature and pre-boot authentication
- Expands security applications through on-board Java applets supported applications
- Secure remote access to VPNs and Web portals
- Secure network logon
- Email encryption
- Digital signing
- Pre-boot authentication

Multiple-Purpose Single Touch

SafeNet eToken 5300 and 5300-C are perfect for enterprises that are serious about security and usability, but want to provide employees with an easy-to-use-and frictionless solution—without multiple PIN entries or bulky form factors. With the Presence Detection feature, enterprise IT can allow easier user experience for employees by requiring user PIN only at logon. In this way, employees can use the advanced functionality of PKI, such as digitally signing documents and encrypting email by simply touching the sensor on the token, saving the user from having to enter a PIN multiple times.

Advanced PKI Advantages

SafeNet eToken 5300 is supported by SafeNet Authentication Client (10.5) and SafeNet eToken 5300-C is supported by SafeNet Authentication Client (10.8) for full local admin and support for advanced token management, events and deployment. In this way, employees can use the advanced functionality of PKI, such as digitally signing documents and encrypting email by simply touching the sensor on the token, saving the user from having to enter a PIN multiple times.

About Thales

The people you rely on to protect your privacy rely on Thales to protect their data. When it comes to data security, organizations are faced with an increasing number of decisive moments. Whether the moment is building an encryption strategy, moving to the cloud, or meeting compliance mandates, you can rely on Thales to secure your digital transformation.

Decisive technology for decisive moments.

Technical Specification

| | SafeNet eToken 5300 Mini and Micro | SafeNet eToken 5300-C | |
|------------------------------|--|--|--|
| Supported operating systems | Windows Server 2019, Windows Server 2016, Windows Server 2012 and 2012 R2, Windows 10 up to and including 21 H1 Windows 8.1, Windows 8, Mac OS, Linux | Windows Server 2019, Windows Server 2016, Windows Server 2012 and 2012 R2, Windows 10 up to and including 21 H1 Windows 8.1, Windows 8, Mac OS, Linux | |
| API & standards support | PKCS#11, Microsoft CAPI and CNG (CSP,KSP), Mac CTK PC/SC, X.509 v3 certificate storage, TLS 1.2 & 1.3, IPSec/IKE | PKCS#11, Microsoft CAPI and CNG (CSP,KSP), Mac CTK PC/SC, X.509 v3 certificate storage, TLS 1.2 & 1.3, IPSec/IKE | |
| Memory size | 80K | 80K | |
| On-board security algorithms | Hash: SHA-256, 384 and 512 RSA: 2048 for SafeNet eToken 5300 Elliptic curves: P-256, P-384 and P-521, ECDSA, ECDH | Hash: SHA-256, 384 and 512 RSA: Up to 4096 for SafeNet eToken 5300-C Elliptic curves: P-256, P-384 and P-521, ECDSA, ECDH | |

| | SafeNet eToken 5300 Mini | SafeNet eToken 5300 Micro | SafeNet eToken 5300-C | |
|--------------------------------|--|---------------------------|-------------------------------------|--|
| Security certifications | FIPS 140-2 level 3 | FIPS 140-2 level 2 | FIPS 140-2 level 3 (SC chip and OS) | |
| Dimensions | 40.5mm*16mm*8mm | 18mm * 12mm*4.5mm | 36.8mm* 12.2mm*6.4mm | |
| ISO specification support | Support for ISO 7816-1 to 4 specifications | | | |
| Operating temperature | 0° C to 70° C (32° F to 158° F) | | | |
| Storage temperature | -40° C to 85° C (-40° F to 185° F) | | | |
| Humidity rating | 0-100% without condensation | | | |
| Water resistance certification | IP X7 – IEC 529 | | | |
| USB connector | USB type A; supports USB 1.1 an | USB type C | | |
| Casing | Hard molded plastic, tamper evident | | | |
| Memory data retention | At least 10 years | | | |
| Memory cell rewrites | At least 500,000 | | | |





